PRODUCT CODE: 830

#### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: 830 PART A PRODUCT CODES: 830 A

**MANUFACTURER: National Polymer** STREET ADDRESS: 9 Guttman Avenue CITY, STATE, ZIP: Charleroi PA 15022

IFORMATION PHONE: 724-483-9300

**EMERGENCY PHONE:** Chemtrec 800-424-9300

FAX PHONE: 724-483-9306

PREPARED BY: Harry Jackson

DATE REVISED: 1/2/15

Chemical Name or Class: Caprolactum mixture

#### **SECTION 2: HAZARDS IDENTIFICATION**

**Hazard Overview** 

GHS Classification: Acute toxicity (Inhalation) Category 4, Acute toxicity (Oral) Category 4, Specific target organ toxicity - single exposure Category 3, Serious eye damage/irritation category 2B, Skin Corrosion/Irritation category 3

**GHS Label Elements and Precautionary Statements:** 

Label Elements: Exclamation Mark



#### **Hazard Statements:**

Warning: May be Harmful if swallowed

Warning: Harmful if inhaled..

Warning: May cause Respiratory irritation

Warning: Causes eye irritation Warning: Causes mild skin irritation.

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.

P330 Rinse mouth.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P332 + P313 IF SKIN irritation occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

Other non-classifiable potential hazards:

Carcinogen category 2

**HMIS HAZARD CLASSIFICATION** 

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

HIGH VAPOR CONCENTRATION CAN CAUSE SEVERE IRRITATION TO THE EYES, NOSE OR THROAT.

CAN CAUSE IRRITATION TO SKIN.

INGESTION:

LIQUID CAN CAUSE IRRITATION TO THE MUCOUS MEMBRANES IF SWALLOWED.

**INHALATION:** 

HIGH VAPOR CONCENTRATION CAN CAUSE SEVERE IRRITATION TO THE RESPIRATORY TRACT.

**HEALTH HAZARDS (ACUTE AND CHRONIC):** 

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENTIZATION OR OTHER ALLERGIC RESPONSES.

PRODUCT CODE: 830

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

**CARCINOGENICITY** 

OSHA: NO NTP: NO IARC: yes

ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - Explanation Of Carcinogenicity: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B. Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
CASTOR OIL	8001-79-4	NONE	NONE	NONE	10-30
2-OXEPANONE, POLYMER WITH 2,2'-OXYBI	S [ETHANOL]				
	36890-68-3	NONE	NONE	NONE	10-30
2-OXYPANONE, 2-ETHYL-2-(HYDROXYMETH	IYL) -1,3-PROPANE	<b>=</b>			
•	37625-56-2	NONE	NONE	NONE	15-40
Precipitated Silica	112926-00-8	NONE	80mg/m3	NONE	0.1-1
Aluminum Oxide Non-fibrous)	1344-28-1	5MG/M3	10MG/M3	NONE	1-5
Sodium oxide	1313-59-3	NONE	NONE	NONE	1-5
Magnesium Oxide	1309-48-4	15mg/m3	10mg/m3	NONE	1-5
Siloxanes and silicones, di-me reactions pro	ducts with silica (	non-hazardous)	_		
	67762-90-7	none	none	none	0.1-1
siloxanes and silicones, di-methyl (non-haza	rdous)				
	63148-62-9	none	none	none	0.1-1
Alkyl Quaternary Ammonium Clay	Proprietary	NONE	NONE	NONE	1-5
Methyl N-Amyl Ketone	110-43-0	100 ppm	50 ppm	none	1-5
Dibutylin Dilurate	77-58-7	0.1mg / m3	0.1mg / m3	0.1mg / m3	0.1-1
Colors may contain:					
Titanium Dioxide	13463-67-7	10mg/m3	10mg/m3	5mg/m3	1-5
*CARBON	1333-86-4	3.5PPM	3.4PPM	NONE	<1.0

SECTION 3 NOTES: "\*" Indicates TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372 ARE PRESENT.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

#### **SECTION 4: FIRST AID MEASURES**

#### **EYES**

IMMEDIATELTY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ATTENTION.

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATLEY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:
DO NOT INDUCE VOMITTING. DILUTE BY GIVING WATER TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:

REMOVE VICTIM TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY.

### **SECTION 5: FIRE-FIGHTING MEASURES**

FLAMMABLE LIMITS IN AIR, UPPER: not available (% by volume) LOWER: not available

FLASH POINT: 200+F METHOD USED: SETA FLASH

**EXTINGUISHING MEDIA:** 

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

**SPECIAL FIRE FIGHTING PROCEDURES:** 

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTERS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER. UNUSUAL FIRE AND EXPLOSION HAZARDS:

PRODUCT CODE: 830

NONE KNOWN.

#### **SECTION 6: RELEASE MEASURES**

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS.

### **SECTION 7: HANDLING AND STORAGE**

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

**OTHER PRECAUTIONS:** 

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **RESPIRATORY PROTECTION:**

NIOSH APPROVED RESPIRATOR REQUIRED TIN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

VENTILATION:

AVOID BREATIHING VAPORS. VENTILLATION MUST BE SUFFICIENT TO CONTROL VAPORS

PROTECTIVE GLOVES:

**IMPERVIOUS GLOVES - NEOPRENE OR RUBBER** 

**EYE PROTECTION:** 

SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

CLEAN BODY COVERING CLOTHING AS WELL AS APRON, FOOTWEAR EQUIPMENT SHOULD BE USED AS DEEMED NECESSARY TO AVOID CONTACT WITH THE MATERIAL.

**WORK HYGIENIC PRACTICES:** 

**OBSERVE GOOD GENERAL HYGIENIC PRACTICES.** 

SEE SECTION THREE FOR OCCPATIONAL EXPOSURE LIMIT VALUES.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE AND ODOR: MEDIUM VISCOSITY CLEAR OR COLORED LIQUID - NEGLIGIBLE ODOR

BOILING POINT OR RANGE: N/A
VAPOR DENSITY (AIR = 1): N/A
SPECIFIC GRAVITY (H2O = 1): 1.1
EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshhold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor Pressure: N/A

Auto Ignition Temperature: N/A

Partition Coefficient: n-octanol/water: N/A Decomposition Temperature: N/A

# **SECTION 10: STABILITY AND REACTIVITY**

#### STABILITY:

**STABLE** 

**CONDITIONS TO AVOID (STABILITY):** 

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

**INCOMPATIBILITY (MATERIAL TO AVOID):** 

AVOID CONTACT WITH STRONG OXIDIZING AGENTS OR MATERIALS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CARBON MONOXIDE, CARBON DIOXIDE AND NITROGEN COMPOUNDS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

No data for the product itself.

Component data:

Component CASTOR OIL CAS# 8001-79-4: Draize test, rabbit, eye: 500 mg Mild; Draize test, rabbit, skin: 100 mg/24H Severe;

Component 2-OXEPANONE, POLYMER WITH 2,2'-OXYBIS [ETHANOL] CAS# 36890-68-3: Oral LD50 (rat) > 2000 mg/kg.

Component 2-OXYPANONE, 2-ETHYL-2-(HYDROXYMETHYL) -1,3-PROPANE CAS# 37625-56-2: Acute oral toxicity - Oral route, LD 50, > 2000 mg/kg. Acute dermal irritation/corrosion - Rabbit, Non irritant (eyes), - Rabbit, Non irritant (skin), Skin irritation –Negligible. Eye irritation Negligible

PRODUCT CODE: 830

Component Titanium Dioxide: Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

Component CAS# 112926-00-8: LD50 (rat >5000 mg/kg, LD50 dermal (rat) >2000 mg/kg

Component Aluminum Oxide CAS# 1334-28-1: Special Remarks on Chronic Effects on Humans: May cause cancer (tumorigenic) according to animal data. No human data found. Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: May cause skin irritation. Eyes: Nuissance Dust. Dust may cause mechanical eye irritation. Inhalation: Nuissance Dust. Material is irritating to mucous membranes and upper respiratory tract. May cause lung injury. Ingestion: May be harmful if swallowed. Ingestion of large amounts mat cause gastrointestinal tract irritation. It is expected to be a low hazard for normal industrial handling.

Component CAS# 112926-00-8, Component Aluminum Oxide CAS# 1334-28-1, Sodium oxide CAS# 1313-59-3 and Magnesium Oxide CAS# 1309-48-4: Components Acute oral toxicity LD50 is greater than 5g/kg (rat). The components are an ocular irritant by FHSA standards. When the components were administered by stomach intubation to male rats, the animals survived single massive doses equivalent to 32.0 gram per kilogram of body weight with good weight gains. There were no significant micropathological findings on tissue taken fourteen days after dosing.

Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg Component Alkyl Quaternary Ammonium Clay CAS# Proprietary: Short term exposure to dust can cause minor irritation or shortness of breath. Eye contact may cause irritation to the eyes due to physical abrasion. Component may cause respiratory disorders or act as an allergen for persons who are strongly allergic to quaternary amines.

Component CAS# 110-43-0: Oral LD 50 (rat): 1600 mg/kg; Oral LD50 (mouse) 730 mg/kg; Inhalation LC50 (rat) 2000-4000 ppm, 4 hr. Dermal LD50 (rabbit) 10206 mg/kg; Dermal LD50 (guinea pig) >16200 mg/kg; Skin irritation (Rabbit) – slight to moderate; Eye irritation (rabbit) slight; Skin sensitization (human) none

Component Dibutylin Dilurate CAS# 77-58-7: ACUTE ORAL TOX (LD50,RAT) 3200.00 MG/KG. ACUTE DERMAL TOX (LD50,RABBIT) >2000 MG/KG (NO DEATHS). ACUTE INHAL TOX (LC50, RAT) >8.10 MG/L/1 HR. AMES TEST: NEG (ACTIVATED & NONACTIVATED) INDUST CHEMS SUC H AS THIS MATL W/ACUTE TOX VALUES SHOWN & WHOSE VAPS/MISTS ARE NOT LIKELY TO BE ENCOUNTERED BY HUMANS WHEN USED IN ANY REASONABLY

FORESEEABLE MANNER WOULD NOT REQ TOXIC LBL ACCORD TO U.S. DOMESTIC & INTERNATIONAL TRANSPORT REQS. IRRIT EFTS DAT: SEV IRRITANT TO EYES OF RABBIT. MOD IRRITANT TO SKIN OF RABBIT.

# **SECTION 12: ECOLOGICAL INFORMATION**

No data for the product itself.

Component data:

Component 2-OXEPANONE, POLYMER WITH 2,2'-OXYBIS [ETHANOL] CAS# 36890-68-3: Fish LC50, 96 hours, 80 mg/l. fish LC50, 96 hours, 39 mg/l. Abiotic degredation: Water, Hydrolysis, t+/- 50 days (calculated value, QSAR) degredation product 6-hydroxycaproic acid. Component 2-OXYPANONE, 2-ETHYL-2-(HYDROXYMETHYL) -1,3-PROPANE CAS# 37625-56-2: Acute toxicity: Fishes, Brachydanio rerio, LC 50, 96h, 150 mg/l. Bactéria, Achromobacter sp., NOEC, 16 h, 670 mg/l. Biodegradation - test ready biodegradability/modified STURM, > 60 %, 7 day (s) Result: readily biodegradable. Remarks - Harmful for aquatic organisms. - Hazard for aquatic environment is limited due to product properties:

- . ready biodegradability.

Component Titanium Dioxide: Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitate (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

Component CAS# 112926-00-8: Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l

Component Aluminum Oxide CAS# 1334-28-1: Products of Biodegradation:Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Component CAS# 112926-00-8, Component Aluminum Oxide CAS# 1334-28-1, Sodium oxide CAS# 1313-59-3 and Magnesium OxideCAS# 1309-48-4: Food Chain Concentration Potential: non expected for components.

Component CAS# 110-43-0: BOD-5: 1770 mg/kg; BOD-20: 2000 mg/kg; COD: 2420 mg/kg. Acute Aquatic Effects: 96 hr LC50 (fathead minnow) 131 mg/l and 48 hr EC50 (daphnia) >90 mg/l (highest concentration tested)

#### **SECTION 13: WASTE DISPOSAL**

WASTE DISPOSAL METHOD:.

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

**SECTION 14: Transport Information** 

**DOT:** Not Regulated

IMO/IMDG: Not Regulated

#### **SECTION 15: REGULATORY INFORMATION**

No data for the product itself.

Component data:

Component CASTOR OIL CAS# 8001-79-4: component is on the TSCA list and Canada DSL

Component 2-OXEPANONE, POLYMER WITH 2,2'-OXYBIS [ETHANOL] CAS# 36890-68-3: Component is on the TSCA list and Canada DSI

PRODUCT CODE: 830

Component 2-OXYPANONE, 2-ETHYL-2-(HYDROXYMETHYL) -1,3-PROPANE CAS# 37625-56-2: TSCA Inventory 8(b): Yes. National Regulations (Canada): Canadian NSN Registration: DSL # 11400. WHMIS Classification: Not Listed. National Regulations (Europe): National Regulations (Europe) EINECS / ELINCS #: EINECS: Not applicable

Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List.

Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN. **Component CAS# 112926-00-8**: Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, TSCA,

Component Aluminum Oxide CAS# 1334-28-1: Federal and State Regulations: Illinois toxic substances disclosure to employee act: Aluminum oxide Rhode Island RTK hazardous substances: Aluminum oxide Minnesota: Aluminum oxide Massachusetts RTK: Aluminum oxide New Jersey: Aluminum oxide New Jersey spill list: Aluminum oxide California Director's list of Hazardous Substances: Aluminum oxide TSCA 8(b) inventory: Aluminum oxide

SARA 313 toxic chemical notification and release reporting: Aluminum oxide Other Regulations: EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances. Other Classifications: WHMIS (Canada): Not controlled under WHMIS (Canada). DSCL (EEC): R36/38- Irritating to eyes and skin. S2- Keep out of the reach of children. S46- If swallowed, seek medical advice immediately **Sodium oxide CAS# 1313-59-3:** Component is on the TSCA list.

Magnesium Oxide CAS# 1309-48-4: Component is on the TSCA list.

Component CAS# 112926-00-8, Component Aluminum Oxide CAS# 1334-28-1, Sodium oxide CAS# 1313-59-3 and Magnesium OxideCAS# 1309-48-4: Components are not classified as a controlled product under regulations pursuant to the federal hazardous product act (e.g. WHMIS)

Component Carbon: Contains Proposition 65 Chemicals .Carbon: is listed on TSCA and DSL Canada

Component Siloxanes and silicones, di-me reactions products with silica: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component siloxanes and silicones, di-methyl: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component Alkyl Quaternary Ammonium Clay CAS# Proprietary: component is on the TSCA, European inventory, Canada DSL, and Australian AICS lists. This component is not known to be a hazardous chemical as defined by OSHA Hazard Communication Standard 29 CFR 1910 1200

Component CAS# 110-43-0: On DSL and TSCA, EINECS, AICS, MITI and ECL lists.

Component Dibutylin Dilurate CAS# 77-58-7: Sara Title III Information: TOXIC SUBSTANCES CONTROL ACT (TSCA): ALL COMPONENTS ARE INCL IN EPA TOXIC SUBSTANCES CTL ACT (TSCA) CHEM SUBSTANCE INVENTORY. OSHA HAZARD COMMUNICATION STD (29CFR1910.1200) HAZARD CLASS(ES): IRRITANT.KIDNEY TOXIN. EPA SARA TITLE III SECTION 312 (40CFR370) HAZARD CLASS. IMMED HLTH HAZARD. EPA SARA TITLE III 313 (40CFR372) TOXIC CHEMICALS "DE MINIMIS" LEVEL ARE NONE. Federal Regulatory Information: CANADA DSL-INCL ON INVENTORY. HAZARD CLASSIFICATION-CLASS D DIVISION 2B..(EEC). EINECS /ELINCS MASTER INVENTORY-INCLUDED ON INVENTORY. EEC SYMBOL-HARMFUL (XN). EEC RISK (R) PHRASES-IRRITATING TO EYES & SKIN (R36/38). HARMFUL BY INHAL (R20). EEC SFTY PHRASES-IN CASE OF CONT W/EYES, RINSE IMMED W/PLENTY OF WATER & SEEK MED ADVICE (S26). AUSTRAILA-AICS-INCLUDED ON INVENTORY. State Regulatory Information: STATE REGS: PROPOSITION 65 SUBSTANCES (COMPONENT(S) KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE TOXICITY & SUBJECT TO WARNING & DISCHARGE REQUIREMENTS UNDER "SAFE DRINKING WATER A ND TOXIC ENFORCEMENT ACT OF 1986"):NONE.

### **SECTION 16: OTHER INFORMATION**

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available
See Section 1 for date of preparation

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION** 

PRODUCT NAME: 830 PART B
PRODUCT CODES: 830 B

MANUFACTURER: National Polymer STREET ADDRESS: 9 Guttman Avenue CITY, STATE, ZIP: Charleroi PA 15022

IFORMATION PHONE: 724-483-9300

EMERGENCY PHONE: Chemtrec 800-424-9300

PREPARED BY: Harry Jackson

DATE REVISED: 1/2/15

Chemical Name or Class: MDI isocyanate

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### **Hazard Overview**

PRODUCT CODE: 830

GHS Classification: Respiratory sensitizer category 1B, Skin corrosion/irritation category 2, skin sensitizer category 1B, Serious eye irritation category 2B, Acute toxicity inhalation category 4, Specific target organ toxicity single exposure category 3, Long term hazard to aquatic environment category 4

GHS Label Elements and Precautionary Statements: Label Elements: Health Hazard Exclamation Mark





#### **Hazard Statements:**

Danger: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Warning: Causes skin irritation

Warning: May cause an allergic skin reaction

Warning: Causes eye irritation
Warning: May be harmful if inhaled

Warning: May cause respiratory irritation.
May cause long lasting harmful effects to aquatic life

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P284 Wear respiratory protection

P280 Wear protective gloves/protective clothing/eye protection/face protection P272 Contaminated work clothing should not be allowed out of the workplace.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area

Response

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P342 + P311 IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician.

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 take off contaminated clothing and wash it before reuse

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P405 Store locked up.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

**HMIS HAZARD CLASSIFICATION** 

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 1 PERSONAL PROTECTIVE EQUIPMENT: G

**POTENTIAL HEALTH EFFECTS** 

**EYES:** 

MAY CAUSE IRRITATION.

SKIN:

MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE. SKIN CONTACT MAY CAUSE SENSITIZATION.

INGESTION:

THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION:

Harmful by inhalation. Irritating to respiratory system. May cause sensitization by inhalation. This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons. The onset of the respiratory symptoms may be delayed for several hours after exposure.

HEALTH HAZARDS (ACUTE AND CHRONIC):

PRODUCT CODE: 830

THERE ARE REPORTS THAT CHRONIC EXPOSURE MAY RESULT IN PERMANENT DECREASE IN LUNG FUNCTION. SINGLE OR REPEATED SKIN CONTACT OR INHALATION MAY CAUSE SENSITIZATION OR ALLERGIC REACTION. PERSONS WITH ASTHMATIC-TYPE CONDITIONS, CHRONIC BRONCHITIS, OTHER CHRONIC RESPIRATORY DISEASES OR RECURRENT SKIN ECXEMA OR SENSITIZATION SHOULD BE EXCLUDED FROM CONTACT TO MATERIALS OR WORKING WITH THIS PRODUCTS. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

**CARCINOGENICITY** 

OSHA: NO NTP: NO IARC: YES

ADDITIONAL CARCINOGENICITY INFORMATION:

Component Diphenylmethane 4,4'-disocyanate CAS# 101-68-8 is a IARC class 3 carcinogen

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

<u>INGREDIENT</u>	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
Isocyanates, reaction product of polyol wi	th methylenedipheny	/l disocyanate			
	9048-57-1	NONE	NONE	NONE	30 - 60
Diphenylmethane 4,4'-disocyanate	101-68-8	0.02ppm	0.005ppm	0.20mg/m3	30 - 60
Homopolymer of methylenediphenyl disor	cyanate	• • •	• •	_	
	25686-28-6	NONE	NONE	NONE	7 - 13

### **SECTION 3 NOTES:**

\*\*\*toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*
Note: Ingredients listed without percentages, the percentages are considered a trade secret.

# **SECTION 4: FIRST AID MEASURES**

EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER OR A POLYGLYCOL BASED SKIN CLEANSER AND REMOVE CONTAMINATED CLOTHING PROMPTLY. INGESTION:

DO NOT INDUCE VOMITING. WASH OUT MOUTH WITH WATER. MOVE EXPOSED PERSON TO FRESH AIR AREA. GET MEDICAL ATTENTION IMMEDIATELY IF SYMPTOMS OCCUR.

INHALATION

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY. OBTAIN MEDICAL ASSISTANCE. TREATMENT IS SYMPTOMATIC FOR PRIMARY IRRITATION OR BRONCHOSPASM.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 4 NOTES:

FOR SEVERE EXPOSURE, MEDICAL FOLLOW-UP SHOULD BE MONITORED FOR AT LEAST 48 HOURS.

### **SECTION 5: FIRE-FIGHTING MEASURES**

FLAMMABLE LIMITS IN AIR, (% by volume) FLASH POINT: 200+F METHOD USED: SETA FLASH UPPER: not available LOWER: not available

**EXTINGUISHING MEDIA:** 

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

**SPECIAL FIRE FIGHTING PROCEDURES:** 

USE FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS. CONTAINERS MAY BURST UNDER INTENSE HEAT. IF WATER IS USED, VERY LARGE AMOUNTS ARE REQUIRED. REACTION BETWEEN WATER AND ISOCYANATE MAY BE VIGOROUS.

PRODUCT CODE: 830

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** 

NO UNUSUAL FIRE HAZARDS KNOW OTHER THEN REACTION TO WATER CAN BE VIGOROUS.

#### **SECTION 6: RELEASE MEASURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING, SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH A LIQUID DECONTAMINANT. FOR LARGE SPILLS. EVACUATE THE AREA AND TEST ATMOSHERE FOR MDI

#### **SECTION 7: HANDLING AND STORAGE**

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS; THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS. STORE MATERIAL BETWEEN 60-100 F AND KEEP DRY.

**OTHER PRECAUTIONS:** 

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **RESPIRATORY PROTECTION:**

USE A NIOSH APPROVED PRESSURE AIR-SUPPLIED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. CARTRIDGE TYPE RESPIRATORS ARE NOT APPROVED FOR PROTECTION AGAINST DIISOCYANATES.

**VENTILATION:** 

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS. HOWEVER, AREA SHOULD BE MONITORED TO PREVENT EXPOSURE BEYOND THE RECOMMENDED OHSA, ACGIH LIMITS.

**PROTECTIVE GLOVES:** 

**IMPERVIOUS GLOVES - NEOPRENE OR RUBBER** 

**EYE PROTECTION:** 

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

**WORK HYGIENIC PRACTICES:** 

**OBSERVE GOOD GENERAL HYGIENIC PRACTICES.** 

SEE SECTION THREE FOR OCCPATIONAL EXPOSURE LIMIT VALUES.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE AND ODOR: MEDIUM VISCOSITY LIQUID BOILING POINT OR RANGE: >300C decomposes

VAPOR DENSITY (AIR = 1): N/A SPECIFIC GRAVITY (H2O = 1): 1.1 EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshhold: N/A

pH: N/A

Melting point/freezing point: N/A

Vapor Pressure: N/A

Auto Ignition Temperature: N/A

Partition Coefficient: n-octanol/water: N/A Decomposition Temperature: N/A

# **SECTION 10: STABILITY AND REACTIVITY**

PRODUCT CODE: 830

STABILITY:

STABLE AT ROOM TEMPERATURE

**CONDITIONS TO AVOID (STABILITY):** 

AVOID EXCESSIVE HEAT, OPEN FLAMES. DUE TO REACTION WITH WATER, A HAZARDOUS BUILDUP OF PRESSURE COULD RESULT.

**INCOMPATIBILITY (MATERIAL TO AVOID):** 

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS, ALCOHOLS, BASES AND WATER.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO, CO2, NITROGEN OXIDES, HYDROCARBONS AND HCN

**HAZARDOUS POLYMERIZATION:** 

POLYMERIZATION MAY OCCUR AT ELEVATED TEMPERATURES IN THE PRESENCE OF ALKALIES, TERTIARY AMINES AND **METAL COMPOUNDS.** 

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Component Diphenylmethane 4,4'-disocyanate CAS# 101-68-8 is a IARC class 3 carcinogen

# **ACUTE TOXICITY:**

Ingredient	Test	Endpoint	Species	Result
Diphenylmethane 4.4'-	OECD 403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat - Male, Female	0.49 mg/l
disocyanate	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabit - Male, Female	>9400 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male	>10000 mg/kg
Homopolymer of methylenediphenyl disocyanate	OECD 403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat - Male, Female	0.49 mg/l
•	OECD 425 Acute Oral Toxicity Up and Down-Procedure	LD50 Oral	Rat - Female	>5000 mg/kg

# IRRITATION/CORROSION

Ingredient	Test	Endpoint	Species
Diphenylmethane 4,4'- disocyanate	OECD 404 Acute Dermal Iritation/ Corrosion	Rabbit	Skin – irritant
,	OECD 405 Acute Eye Irritation/ Corrosion	Eyes	Non-Irritant
Homopolymer of methylenediphenyl disocyanate	OECD 405 Acute Eye Irritation/ Corrosion	Eyes	Non-irritant
	OECD 404 Acute Dermal Irritation/ Corrosion	Rabbit	Skin – Irritant
	OECD 404 Acute Dermal Irritation/ Corrosion	Other	Non Corrosive

Conclusion/ Summary

disocyanate

Skin: Isocyanates, reaction product of polyol with methylenediphenyl

No Additional Information

Diphenylmethane 4,4'- irritating to skin

disocyanate
Homopolymer of irritating to skin methylenediphenyl disocyanate

Eyes:

Isocyanates, reaction No additional Information product of polyol with

methylenediphenyl
disocyanate

Diphenylmethane 4,4'Diisocyanate

Based on the human occupational exposure data, this substance
is considered as irritating to eyes.

Homopolymer of irritating to the eyes methylenediphenyl disocyanate

Respiratory

Isocyanates, reaction No additional Information

product of polyol with methylenediphenyl disocyanate Diphenylmethane 4,4'-

Diphenylmethane 4,4'disocyanate
Homopolymer of
methylenediphenyl

No additional information
No additional information

Sensitizer

disocyanate

Sensitizer				
Ingredient	Test	Route of Exposure	Species	Result
Diphenylmethane 4,4'-	OECD 429 Skin	Skin	Mouse	Sensitizing
disocyanate	Sensitization:			
	Local Lymph	Skin	Cuinas nia	Non consitining
	Node Assay	SKIN	Guinea pig	Non sensitizing
	OECD 406 Skin	Respiratory	Guinea pig	Sensitizing
	Sensitization			
	No official			
	guidelines			
Homopolymer of	OECD 406 Skin	Skin	Guinea pig	Sensitizing
methylenediphenyl disocyanate	Sensitization	Respiratory	Guinea pig	Sensitizing
	No official			
	guidelines			

PRODUCT CODE: 830

Mutagenicity

Ingredient	Test	Result
Diphenylmethane 4.4'-	Experiment: In vitro	Negative
disocyanate	Subject: Bacteria	
	Metabolic activation: +/-	Negative
	Experiment: In vivo	
	Subject: Mammalian-Animal	
Homopolymer of methylenediphenyl	Experiment: In vitro	Negative
disocyanate	Subject: Bacteria	
	Metabolic activation: +/-	
	Experiment: In vivo	
	Subject: Mammalian-Animal	

PRODUCT CODE: 830

# Conclusion/Summary

Diphenylmethane 4,4'-diisocyanate No mutagenic effect.

#### Carcinogenicity

Ingredient	Test	Species	Dose	Exposure	Result/ Result type
Diphenylmethane 4,4'- disocyanate	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat – Male, Female	1 mg/m3	2 years; 5 days per week	Positive - Inhalation - NOAEL
Homopolymer of methylenediphenyl disocyanate	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat – Male, Female	1 mg/m3	2 years; 5 days per week	Negative - Inhalation - NOAEL

#### Conclusion/Summary:

Diphenylmethane 4,4'-diisocyanate - No known significant effects or critical hazards.

Teratogenicity

Ingredient	Test	Species	Result/Result Type
Diphenylmethane 4,4'- disocyanate	OECD 414 Prenatal	Rat – Female	Negative – Inhalation
disocyanate	Developmental		
	Toxicity Study		
Homopolymer of	OECD 414 Prenatal	Rat – Male, Female	Negative - Inhalation
methylenediphenyl disocyanate	Developmental		
	Toxicity Study		

### Conclusion/Summary:

#### Potential acute health effects

**Inhalation :** LC50 (rat) : ca. 490 mg/m³ (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns. This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may

include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons.

Ingestion: Low oral toxicity. Ingestion may cause irritation of the gastrointestinal tract.

**Skin contact:** Irritating to skin. May cause sensitisation by skin contact Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitisers including disocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.

Eye contact: Irritating to eyes.

#### **Potential Chronic Health Effects:**

Ingredient	Test	Endpoint	Species	Result
Homopolymer of methylenediphenyl	OECD 453	Chronic NOEC	Rat – Male, Female	0.2 mg/m³
disocyanate	Combined Chronic	Inhalation Dusts and		
	Toxicity/	Mists		
	Carcinogenicity		Rat – Male, Female	
	Studies			
	OECD 413	Sub-chronic NOEC		<4 mg/m³
	Subchronic	Inhalation Dusts and		
	Inhalation Toxicity:	mists		
	90-day Study			

PRODUCT CODE: 830

General: No known significant effects or critical hazards.

Target Organs: No known significant effects or critical hazards.

Carcinogenicity: Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m3), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m3 and no effects at 0.2 mg/m3. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.

**Mutagenicity** There is no substantial evidence of mutagenic potential. No birth defects were seen in two independant animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother. Fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations, which are well in excess of defined occupational exposure limits.

Teratogenicity Developmental effects: No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards

# Medical conditions aggravated by over-exposure

None known

# **SECTION 12: ECOLOGICAL INFORMATION**

**Environmental effects:** By comparison with an analogous product, the following values are anticipated. The measured ecotoxicity is that of the hydrolised product, generally under conditions maximising production of soluble species. Even so, the observed ecotoxicity is low/very low. A pond study showed gross contamination caused no significant toxic effects on a wide variety of flora in all trophic levels (including fish), no detectable

diaminodiphenylmethane (MDA), and no evidence of bioaccumulation of MDI or MDA.

#### Aquatic Toxicity

Ingredient 7	Test	Endpoint	Exposure	Species	Result
4,4'- disocyanate	OECD 202 <i>Daphnia</i> sp. Acute	Acute EC50	25 hours static		

		Acute LC50	06 hours statio	
	Immobilisation	Acute LC50	96 hours static	
	Test	Observation NOTO	04 45	
	OECD 203 Fish,	Chronic NOEC	21 days semi- static	
	Acute			
	Toxicity Test			
	OECD 211			
	Daphnia Magna			
	Reproduction			
	Test	Observite NIOFO	70 h	
Homopolymer of	OECD 201 Alga,	Chronic NOEC	72 hours static	
methylenediphenyl	Growth	5050	70.1	
disocyanate	Inhibition Test	Acute EC50	72 hours static	
	OECD 201 Alga,			
	Growth	Acute EC50	3 hours static	
	Inhibition Test			
	OECD 209			
	Activated	Acute EC50	24 hours static	
	Sludge,			
	Respiration			
	Inhibition Test	Acute LC50	96 hours static	
	OECD 202	Acute LC30	90 Hours static	
	Daphnia sp.	Chronic NOEC	21 days semi-	
	Acute	Chionic NOEC	static	
	Immobilisation			
	Test			
	OECD 203 Fish,			
	Acute			
	Toxicity Test			
	OECD 211			
	Daphnia Magna			
	Reproduction			
	Test			
Diphenylmethane-	OECD 209	Acute EC50	3 hours static	
2,4'-	Activated			
diisocyanate	Sludge,			
	Respiration	Acute EC50	24 hours static	
	Inhibition Test	Acute 2000	24 Hours static	
	OECD 202			
	Daphnia sp.			
	Acute	Acute LC50	96 hours static	
	Immobilisation			
		Chronic NOEC	24 hours semi- static	
	Test		Statio	
	OECD 203 Fish,			
	Acute			
	Toxicity Test			
	OECD 211			
	Daphnia Magna Reproduction			
	1.eproduction			

<b>-</b> ,		
Test		
1031		

PRODUCT CODE: 830

Persistence and degradability

Ingredient	Test	Period	Result
Diphenylmethane 4,4'- diisocyanate OECD 302C Inherent Biodegradability: Modified MITI Test (II) 28 days 0 %	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 days	0%
Homopolymer of methylenediphenyl diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 days	0%
Diphenylmethane-2,4'- diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 days	0%

Conclusion/Summary: Diphenylmethane 4,4'-diisocyanate - Not biodegradable

Ingredient	Aquatic half life	Photolysis	Biodegradability
	Fresh water 0.83 days	-	A
Diphenylmethane 4,4'-			Not readily
diisocyanate			
OECD 302C Inherent			
Biodegradability:			
Modified MITI Test (II)			
28 days 0 %			
Homopolymer of	Fresh water 0.83 days	-	Not Readily
methylenediphenyl			
diisocyanate			
Diphenylmethane-2,4'-	Fresh water 0.83 days	-	Not Readily
diisocyanate			

# Bioaccumulative Potential

Ingredient	LogPow	BCF	Potential
Diphenylmethane 4,4'- diisocyanate OECD 302C Inherent	4.51	200-	Low
Biodegradability: Modified MITI Test (II) 28 days 0 %			
Homopolymer of methylenediphenyl diisocyanate	8.56	-200	Low

Diphenylmethane-2,4'-	4.51	-200	Low
diisocyanate			

#### Mobility in soil:

**Mobility** By considering the production and use of the substance, it is unlikely that significant environmental exposure in the air or water will arise. Immiscible with water, but will react with water to produce inert and non-biodegradable solids. Conversion to soluble products, including diamino- diphenylmethane (MDA), is very low under the optimal laboratory conditions of good dispersion and low concentration. In air, the predominant degradation process is predicted to be a relatively rapid OH radical attack, by calculation and by analogy with related diisocyanates.

PRODUCT CODE: 830

:

Other adverse effects: No known significant effects or critical hazards.

BOD5 Not Determined COD Not Determined TOC Not Determined

#### **SECTION 13: WASTE DISPOSAL**

#### **WASTE DISPOSAL METHOD:**

DISPOSE OF MATERIAL ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

# **SECTION 14: Transport Information**

DOT: Not Regulated (single containers less than 5,000 pounds)

IMO/IMDG: Not Regulated

### **SECTION 15: REGULATORY INFORMATION**

Component(s) 4,4'-DIPHENYLMETHANE DIISOCYANATE CAS# 101-68-8 and Modified MD CAS# NOT LISTED: This material is classified as hazardous under OSHA hazard communication standard 29 CFR 1910.1200. HCS Classification: Class – Toxic, Irritating substance, Sensitizing substance. Components are on the TSCA list. Canadian Regulations: This product has been classified in accordance with the hazard criteria of the CPR (controlled Products Regulations) Class D-1A Material Causing immediate and serious toxic effects (very toxic). Class D-2A Material causing other toxic effects (Very Toxic). Class D-2b material causing other toxic effects (Toxic).

# **SECTION 16: OTHER INFORMATION**

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

#### Label requirements

Harmful by inhalation. Irritating to eyes and respiratory system. May cause sensitization by inhalation and skin contact. This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitised persons. The onset of the respiratory symptoms may be delayed for several hours after exposure.

Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

N/A = Not Available See Section 1 for date of preparation