

# SAFETY DATA SHEET

PRODUCT CODE: 903SL Pigment tan

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** NP903SL Pigment tan  
**PRODUCT CODES:** 903SL Pigment tan

**MANUFACTURER:** National Polymers Inc.  
**STREET ADDRESS:** 9 Guttman Avenue  
**CITY, STATE, ZIP:** Charleroi, Pa. 15022

**INFORMATION PHONE:** 724-483-9300  
**EMERGENCY PHONE:** Chemtrec 800-424-9300  
**FAX PHONE:** 724-483-9306

**PREPARED BY:** Harry Jackson

**DATE REVISED:** 4/5/18

**Chemical Name or Class:** dry pigment blend

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

**GHS Classification:** Carcinogenicity category 1,

**GHS Label Elements and Precautionary Statements:**

Label Elements: Health hazard



Hazard Statements:  
DANGER: May cause cancer

### Precautionary statements:

P102 Keep out of reach of children.  
P103 Read label before use  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/protective clothing/eye protection/face protection

### Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

### Storage:

P405 Store locked up

### Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

### HMIS HAZARD CLASSIFICATION

**HEALTH:** 1      **FLAMMABILITY:** 0      **REACTIVITY:** 0      **PERSONAL PROTECTIVE EQUIPMENT:** E

### POTENTIAL HEALTH EFFECTS

#### EYES:

MAY CAUSE REDDENING OF THE EYES OR EYE IRRITATION.

#### SKIN:

MAY CAUSE SKIN IRRITATION

#### INGESTION:

NONE KNOWN

#### INHALATION:

PROLONGED EXPOSURE TO RESPIRABLE CRYSTALLINE QUARTZ MAY CAUSE DELAYED LUNG INJURY (SILICOSIS). ACUTE OR RAPIDLY DEVELOPING SILICOSIS MAY OCCUR IN A SHORT PERIOD OF TIME IN HEAVY EXPOSURE IN SOME APPLICATIONS SUCH AS SAND BLASTING.

#### HEALTH HAZARDS (ACUTE AND CHRONIC):

MAY CAUSE DELAYED SILICOSIS OR RAPID SILICOSIS IN SOME OCCUPATIONS SUCH AS SANDBLASTING, SILICOSIS IS A FORM OF A DISABLING PULMONARY FIBROSIS WHICH CAN BE PROGRESSIVE AND COULD LEAD TO DEATH. INHALATION MAY LEAD TO LUNG SCARRING AND MASSIVE FIBROSIS WHICH COULD BE ACCOMPANIED BY RIGHT HEART ENLARGEMENT, HEART FAILURE, OR PULMONARY FAILURE, SMOKING AGGRAVATES THE EFFECTS OF EXPOSURE.

#### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS CAN BE AGGRAVATED BY EXPOSURE

#### CARCINOGENICITY

OSHA: NO      NTP: YES      IARC: YES

# SAFETY DATA SHEET

PRODUCT CODE: 903SL Pigment tan

## ADDITIONAL CARCINOGENICITY INFORMATION:

IARC HAS DETERMINED THAT CRYSTALLINE SILICA INHALED IN THE FORM OF QUARTZ IS CARCINOGENIC TO HUMANS (GROUP 1- CARCINOGENIC TO HUMANS). THE NTP CLASSIFIES RESPIRABLE CRYSTALLINE SILICA AS REASONABLY ANTICIPATED TO BE A CARCINOGEN.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
*SILICON DIOXIDE	14808-60-7	0.05 mg/m3	0.025 mg/m3	0.05 mg/m3	60-100
Titanium Dioxide	13463-67-7	10mg/m3	10mg/m3	5mg/m3	20-35
iron oxide	1317-61-9	10mg/m3	0.2mg/m3	NONE	2-7
red 101	1309-37-1	10mg/m3	0.25 mg/m3	NONE	<1
Yellow MIO	51274-00-1	5mg/m3	15mg/m3	NONE	9-15

\*\*\*\* indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

FOLLOW OSHA HAZARD COMMUNICATION RULE 29CFR SECTIONS 1910.1200, 1915.99, 1917.28, 1918.9, 1926.59, AND STATE AND LOCAL COMMUNITY RIGHT TO KNOW LAWS.

Note: Ingredients listed without percentages, the percentages are considered a trade secret. Other components below reportable levels < 10%

## SECTION 4: FIRST AID MEASURES

### EYES:

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### SKIN:

Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

### INGESTION:

Rinse mouth. Get medical attention if symptoms occur.

### INHALATION:

Move to fresh air. Call a physician if symptoms develop or persist.

### NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

Provide general supportive measures and treat symptomatically.

## SECTION 5: FIRE-FIGHTING MEASURES

**FLAMMABLE LIMITS IN AIR,**  
(% by volume)

**UPPER:** not available

**LOWER:** not available

**FLASH POINT<sup>o</sup> F:** N/A

**METHOD USED:**

N/A

### EXTINGUISHING MEDIA:

Water fog, Foam, Dry Chemical, Carbon dioxide

### SPECIAL FIRE FIGHTING PROCEDURES:

CRYSTALLINE SILICA BLEND IS NEITHER A FIRE NOR AN EXPLOSION HAZARD. DURING FIRE, GASSES HAZARDOUS TO HEALTH MAY BE FORMED. USE FOAM, CO2, DRY CHEMICAL, WATER FOG.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

## SECTION 6: RELEASE MEASURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND USE DUSTLESS HANDLING EQUIPMENT TO CLEAN UP LARGE SPILLS, PLACE IN SUITABLE CONTAINERS FOR DISPOSAL.

## SECTION 7: HANDLING AND STORAGE

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL DRY PLACE. PROPERLY LABEL ALL CONTAINERS AND RESEAL ALL PARTIALLY USED CONTAINERS. AVOID CREATING ANY DUST WHEN WORKING WITH THIS MATERIAL.

### OTHER PRECAUTIONS:

AVOID BREATHING DUST GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. PROVIDE TRAINING FOR YOUR EMPLOYEES RELATING TO OCCUPATIONAL EXPOSURE TO QUARTZ DUST. SEE ASTM STANDARD E1132-86 STANDARD PRACTICE FOR HEALTH REQUIREMENTS RELATING TO EXPOSURE TO QUARTZ DUST. IF BETTER THAN 500 X PEL USE A SELF CONTAINED BREATHING APPARATUS. IF SANDBLASTING, USE ANY TYPE CE SUPPLIED AIR RESPIRATOR WITH FULL FACE PIECE OR HOOD. STORE LOCKED UP.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****RESPIRATORY PROTECTION:**

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO QUARTZ DUST. PROVIDE SUFFICIENT EXHAUST TO KEEP EXPOSURE LEVELS BELOW THE ACGIH PEL.

**VENTILATION:**

USE EXHAUST SUFFICIENT TO MAINTAIN AIRBORNE PARTICULATES BELOW THE ACGIH PEL LIMITS ESTABLISHED.

**PROTECTIVE GLOVES:**

WEAR CHEMICAL RESISTANT GLOVES.

**EYE PROTECTION:**

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

PROVIDE ANY EQUIPMENT NECESSARY TO PREVENT THE INHALATION OF QUARTZ DUST.

**WORK HYGIENIC PRACTICES:**

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Crystalline SiO <sub>2</sub> (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m <sup>3</sup>	Total dust.
		2.4 millions of particle	respirable

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Crystalline SiO <sub>2</sub> (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Crystalline SiO <sub>2</sub> (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>	Respirable dust.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE AND ODOR:** Powder GRANULAR CRUSHED OR GROUND - tan - no odor

**BOILING POINT OR RANGE ° F:** N/A

**VAPOR DENSITY (AIR = 1):** N/A

**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** 2.0-2.5

**EVAPORATION RATE:** N/A

**SOLUBILITY IN WATER:** INSOLUBLE IN WATER

**Odor Threshold:** N/A

**pH:** N/A

**Melting point/freezing point:** N/A

**Vapor Pressure:** N/A

**Auto Ignition Temperature:** N/A

**Partition Coefficient: n-octanol/water:** N/A

**Decomposition Temperature:** N/A

**SECTION 10: STABILITY AND REACTIVITY****STABILITY:**

STABLE

# SAFETY DATA SHEET

PRODUCT CODE: 903SL Pigment tan

## CONDITIONS TO AVOID (STABILITY):

CONTACT WITH POWERFUL OXIDIZING AGENTS SUCH AS FLUORINE, CHLORINE, TRIFLUORIDE, MANGANESE TRIOXIDE, OXYGEN TRIFLUORIDE

## INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS

## HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SILICA WILL DISSOLVE IN HYDROCHLORIC ACID TO FORM A CORROSIVE GAS- SILICON TETRAFLUORIDE

## HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

### Information on likely routes of exposure

#### Ingestion

Expected to be a low ingestion hazard.

#### Inhalation

Prolonged inhalation may be harmful.

#### Skin contact

May cause skin irritation.

#### Eye contact

May cause eye irritation.

### Information on toxicological effects

#### Acute toxicity

Not available.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

#### Respiratory sensitization

Not available.

#### Skin sensitization

This product is not expected to cause skin sensitization.

### Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) May cause cancer. According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline SiO<sub>2</sub> (Quartz) (CAS 14808-60-7) Carcinogenic to humans.

### US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline SiO<sub>2</sub> (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

### Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

### Specific target organ toxicity - single exposure

Not classified.

### Specific target organ toxicity - repeated exposure

Not classified.

### Aspiration hazard

Not available.

### Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

No data for the product itself.

### Component data:

**Component Silicon Dioxide:** There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

# SAFETY DATA SHEET

PRODUCT CODE: 903SL Pigment tan

The product itself and its products of degradation are not toxic.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

## SECTION 13: WASTE DISPOSAL

---

### WASTE DISPOSAL METHOD:

This product is not classified as a hazardous waste under the authority of the RCRA (40CFR261) or CERCLA (40CFR 117&302) **DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.**

---

## SECTION 14: Transport Information

---

**DOT:** Not Regulated

**IMO/MDG** Not regulated

---

## SECTION 15: REGULATORY INFORMATION

---

### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline SiO<sub>2</sub> (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

TSCA Status: All components Listed or exempt

DSL Status: All components Listed or exempt

CERCLA Reportable Quantity: Listed at 40 CFR 302.4

RCRA Status: If discarded in its purchased form, this product would not be a Hazardous waste either by listing or by characteristic. However, Under RCRA, it is the responsibility of the product user to Determine at the time of disposal, whether a material containing The product or derived from the product should be classified as a Hazardous waste. (40 CFR 261.20-24).

SARA Title III:

Section 302 Extremely Hazardous Substances: None

Section 311/312 Hazard Categories: Acute and Chronic

Section 313 Toxic Chemicals: None.

---

## SECTION 16: OTHER INFORMATION

---

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation