NP915 TECHNICAL DATA (Easy Cleaner)

PRODUCT DESCRIPTION:

This product is a heavy duty cleaner formulated for versatility and dependability. Its' uses can encompass anything from floor cleaning to hot dip tank cleaning. Worker safety is an integral part of the manufacturing process and this product contains no caustics, butyl ethers, or chlorinated and petroleum based solvents. Unlike many industrial strength cleaners, NP915 is 100% biodegradable and environmentally safe. The versatility of this product is enhanced by complete water reducibility to assure the capability to customize the cleaning strength to meet your specific needs. NP915 is a concentrated non-flammable detergent that dissolves a wide range of greases and oil based soils while leaving the area with a refreshing citrus scent. Terpene hydrocarbons, the major component of oranges, and naturally occurring, are used in this product. As a water reducible cleaner, the ability to work with and around most metals is assured by the addition of flash rust additives and inhibiters. This product is compatible with most industrial coatings including epoxies and urethanes.

THIS PRODUCT IS RECOMMENDED FOR:	
TRUCKING FLEETS	U.S. POST OFFICES
PRINTING PLANTS	FOUNDRIES
STEEL MILLS	WASTE CLEAN UP FIRMS
CONTRACT CLEANING FIRMS	METAL FABRICATORS
MANUFACTURERS	MILITARY INSTALLATIONS

DIRECTIONS FOR USE:

For heavy duty cleaning and degreasing, we recommend 1 part NP915 to 4 parts water by volume. Deviations from this ratio can employ differing concentrations suited to the cleaning strength needed. For less soiled floors, dilute with more water and for heavily soiled floors, dilute with less water. Ratios varying from 1:1 to 50:1 (Water: NP915) can be used for cleaning.

APPLICATION PROCEDURE:

For cleaning- dilute NP915 to the desired strength and apply to the surface with a mopping action. Allow the solution to remain on the floor for approximately five minutes. Remove the loosened grime and dirt by mopping and then rinse the floor with clean water. For walls, woodwork, and enameled surfaces, apply the diluted NP915 directly by a sponge of cloth. Rinse the surface with a clean water dampened cloth or sponge. Always check product compatibility before using.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommenced herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.

COPYRIGHT1/1/11.