

SAFETY DATA SHEETS

NP866T, High Solids, Moisture-Cured, Industrial Maintenance Coating, Clear

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME/CODE: NP866T, Clear

MANUFACTURER: National Polymers Inc.
STREET ADDRESS: 9 Guttman Avenue
CITY, STATE, ZIP: Charleroi, Pa. 15022

INFORMATION PHONE: 724-483-9300 **EMERGENCY PHONE:** Chemtrec 800-424-9300 **FAX PHONE:** 724-483-9306

PREPARED BY: Harry Jackson

DATE REVISED: 4/26/19

Chemical Name or Class: Aliphatic Urethane Pre-polymer mixture

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Acute oral toxicity category 4, Respiratory sensitizer category 1, Skin sensitizer category 1, Flammable liquid category 3, Specific target organ toxicity single exposure category 3, Specific target organ toxicity following repeated exposure category 1, Skin corrosion/irritation category 2, Toxic to reproduction category 2, Germ cell Mutagenicity category 1B, Serious Eye damage/Irritation Category 2A, Carcinogenicity category 1a, Acute hazard to aquatic environment category 3, Chronic hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Flame, Health Hazard Exclamation Mark, Aquatic Toxicity,



Hazard Statements:

Warning: Harmful if swallowed.
Danger: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Warning: May cause an allergic skin reaction.
Warning: Flammable Liquid and Vapour.
Warning: May cause respiratory irritation.
Danger: Causes damage to organs through prolonged or repeated exposure.
Warning: Causes skin irritation.
Warning: Suspected of damaging fertility or the unborn child.
Danger: May cause genetic defects.
Warning: Causes serious eye irritation.
Danger: May cause cancer.
Harmful to aquatic life
Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.
P103 Read label before use
P261 Avoid breathing dust/fume/gas/mist/vapours/spray
P284 Wear respiratory protection.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves and clothing to prevent skin contact.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/...equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray
P271 Use only outdoors or in a well-ventilated area.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

SAFETY DATA SHEETS

NP866T, High Solids, Moisture-Cured, Industrial Maintenance Coating, Clear

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

Response

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P342 + P311 IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P370 + P378 In case of fire: Use **ALCOHOL FOAM, CO2, DRY CHEMICAL** for extinction

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state federal or international laws

Other non-classifiable hazards based on ingredients: Acute inhalation toxicity category 2

HMIS HAZARD CLASSIFICATION

HEALTH: 2 **FLAMMIBILITY: 2** **REACTIVITY: 1** **PERSONAL PROTECTIVE EQUIPMENT: G**

POTENTIAL HEALTH EFFECTS

EYES:

Can cause irritation, redness, tearing, or blurred vision as well as corneal opacity and conjunctivitis.

SKIN:

May cause irritation, defatting and dermatitis.

INGESTION:

Can cause gastrointestinal irritation, nausea, vomiting, diarrhea and aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Can cause corrosive action to mucous membranes and digestive tract.

INHALATION:

Can cause nausea and respiratory irritation, dizziness, weakness, fatigue, headache and possible unconsciousness. Burning sensation to mucous membranes, shortness of breath and flu like symptoms may occur.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Can cause sensitization by exposure through contact or high concentrations of vapor. Overexposure can possibly cause anemia. Liver abnormalities, kidney damage or eye damage. May cause asthma or other respiratory disorders, bronchitis, emphysema, hyperactivity and eczema. Chronic Inhalation: as a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma), which will cause them to react to a later exposure to isocyanate at levels well below the TLV or MGL. These symptoms, which include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed up to several hours after exposure. Similar to many nonspecific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can persist for weeks and in several years. Chronic overexposure to isocyanates has been reported to cause lung damage, including decrease in lung function, which may be permanent. Sensitization may either be temporary or permanent. Acute skin Contact: Isocyanates react with the skin protein and moisture and can cause irritation. Symptoms of skin irritation may be reddening, swelling, rash, scaling, or blistering. Some persons may develop skin sensitization from skin contact. Cured material is difficult to remove.

Chronic Skin contact: Prolonged contact with the isocyanate can cause reddening, swelling, rash, scaling, or blistering. In those who have developed a skin sensitization, these symptoms can develop as a result of contact with very small amounts of liquid material or even as a result of vapor-only exposure.

SAFETY DATA SHEETS

NP866T, High Solids, Moisture-Cured, Industrial Maintenance Coating, Clear

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE.

CARCINOGENICITY

OSHA: no NTP: no IARC: no

ADDITIONAL CARCINOGENICITY INFORMATION:

No data

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
1-Methoxy-2-Propyl Acetate	108-65-6	100ppm	100ppm	NONE	10-30
4-chlorobenzotrifluoride	98-56-6	100ppm	100 ppm	NONE	5-15
Aliphatic Isocyanate	5124-30-1	0.005ppm	0.005ppm	NONE	<0.5
Aliphatic Urethane Prepolymer	Non available	NONE	NONE	NONE	60-100

SECTION 3 NOTES:

*** Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret. Information concerning non-hazardous ingredients are considered a trade secret.

SECTION 4: FIRST AID MEASURES

EYES:

Flush eyes with water for at least fifteen minutes and consult a physician.

SKIN:

For extreme exposure use a safety shower immediately. Wash affected skin with soap and water and remove all contaminated clothing promptly.

INGESTION:

If swallowed, contact a physician immediately. Do not induce vomiting. Decision to induce vomiting should only be made by a physician. Never give anything by mouth to an unconscious person.

INHALATION:

Remove victim to fresh air and administer oxygen if necessary. Obtain medical assistance. Asthmatic type symptoms may occur immediately or be delayed for several hours. Treatment is symptomatic.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

This product contains aromatic and aliphatic hydrocarbon solvents and aliphatic isocyanate.

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR,
(% by volume)

UPPER: 13 percent
LOWER: 1 percent

FLASH POINT: 110F

METHOD USED:

Closed cup

EXTINGUISHING MEDIA:

Foam, alcohol foam, co2, dry chemical

SPECIAL FIRE FIGHTING PROCEDURES:

Do not enter confined fire area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus. Presence of solvents in products may require grounding. Remove all sources of ignition.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

If fire occurs, solvents may produce excessive pressure. Sealed drums may rupture and ignite. Vapors are heavier than air and may travel along the ground and ignite by any source of ignition. During a fire, TDI vapors and other toxic gasses may be evolved such as CO, CO₂, N₂O, HCN, unburned hydrocarbons, and toxic fumes.

SAFETY DATA SHEETS

NP866T, High Solids, Moisture-Cured, Industrial Maintenance Coating, Clear

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Personnel Safeguards: Immediately evacuate all non-essential personnel to safe places. Emergency responders should wear positive pressure supplied air respirator with full face piece and proper protective gear before entering the affected area. Regulatory Notifications: Waste of this product is defined as hazardous according to U.S. EPA. Spill reporting requirements and reportable quantities vary by region. Consult all applicable state and local regulations. For Canada, observe all precautions noted above.

Containment and Clean-up: Remove all sources of ignition. Provide ventilation. Respiratory protection is recommended during spill clean-up. Stop leak if possible without risk. Prevent liquids from entering sewers, drains or waterways by diking with sand or earth. Absorb with vermiculite or other absorbent material, then flush area with decontamination solution. Put in open drums. Treat and clean with decontamination solution consisting of water containing 4-8% ammonia and 2% detergent.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in a cool dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Mixed materials contain the hazards of all the components, therefore, read the SDS's of all the components prior to using material. Properly label all containers. Keep material away from all sources of ignition. Wear appropriate safety equipment and protective clothing.

OTHER PRECAUTIONS:

Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles cannot be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof. Wear appropriate safety equipment and respirator at all times when ventilation is not sufficient to control vapors. Observe OSHA regulations for respirator use (29 CFR 1910.134). When spraying material avoid exposure to all mists generated by using air supplied respirator.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Use a NIOSH approved respirator as required to prevent over exposure to vapor in accordance with 29 CFR 1910.134. Engineering or administrative measures should be taken to reduce the risk and exposure. Use a positive pressure supplied air respirator when exceeding TLV's or if TDI monomer concentrations exceed acceptable limits of when spraying material.

VENTILATION:

Exhaust ventilation sufficient to keep airborne concentrations of TDI below their TLV and MGI maximum. Refer to Patty's industrial hygiene and toxicology – volume 1 (3rd edition) chapter 17 and volume III (1st edition) chapter 3 for details

PROTECTIVE GLOVES:

Impervious gloves – neoprene or rubber

EYE PROTECTION:

Splash goggles or glasses with side shields. Do not wear contact lenses when using this product.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear body covering clothing and other coverings as necessary such as apron and appropriate footwear to avoid contact with material.

WORK HYGIENIC PRACTICES:

Observe good general hygienic practices.

Exposure Limits and Guidelines Component	CAS No.	Exposure Limit
1-methoxy-2-propyl acetate	108-65-6	0.05 mg/m ³ TWA, NIOSH
Aliphatic isocyanate	5024-30-1	0.005ppm OSHA PEL
parochlorobenzotrifluoride	98-56-6	100ppm ACGIH TWA

SEE SECTION THREE FOR ADDITIONAL OCCUPATIONAL EXPOSURE LIMIT VALUES.

SAFETY DATA SHEETS

NP866T, High Solids, Moisture-Cured, Industrial Maintenance Coating, Clear

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: High viscosity liquid with typical solvent odor.

BOILING POINT OR RANGE: 284-500 F

VAPOR DENSITY (AIR = 1): Not Determined

SPECIFIC GRAVITY (H₂O = 1): 1.1

EVAPORATION RATE: Not Determined

SOLUBILITY IN WATER: Negligible

Odor Threshold: Not Determined

pH: Not Applicable

Melting point/freezing point: Not determined

Vapor Pressure: 3.7 mm Hg @ 20C

Auto Ignition Temperature: Not determined

Partition Coefficient: n-octanol/water: Not determined

Decomposition Temperature: Not determined

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

Stable

CONDITIONS TO AVOID (STABILITY):

Avoid excessive heat or open flames as well as all sources of ignition such as sparks, heaters, and static discharges etc.

INCOMPATIBILITY (MATERIAL TO AVOID):

Avoid water, amines, strong bases, alcohols, metal compounds, and surface active compounds.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

May form toxic chemicals, carbon dioxide, carbon monoxide, oxides of nitrogen, HCN and HDI

HAZARDOUS POLYMERIZATION:

Moisture of materials that react with isocyanates and temperatures above 400 degrees f may cause polymerization.

SECTION 11: TOXICOLOGICAL INFORMATION

Primary Eye Irritation: Irritating

Primary Skin Irritation: Irritating

Acute Dermal Toxicity: Not available

Subacute Dermal Toxicity: Not available

Dermal Sensitization: Not available

Inhalation Toxicity: Not available

Inhalation Sensitization: Not available

Oral Toxicity: Mutagenicity: Not available

Carcinogenicity: Diisocyanates are suspect carcinogens. When ingested, diisocyanates have caused cancer in certain animals.

Reproductive Toxicity: Not available

Teratogenicity: Not available

Immunotoxicity: Not available

Neurotoxicity: Not available

No other toxicological information available

SECTION 12: ECOLOGICAL INFORMATION

Aquatic Toxicity: Not known.

Terrestrial Toxicity: Not known

Chemical Fate and Transport: Not known.

No other ecological information available

SAFETY DATA SHEETS

NP866T, High Solids, Moisture-Cured, Industrial Maintenance Coating, Clear

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:

Dispose of the material in a waste disposal site in accordance with local, state, and federal law.

SECTION 14: Transport Information

DOT: UN1263, Paint (CONTAINS 1-Methoxy-2-Propyl Acetate), 3, PG III, Marine Pollutant

Other: Not regulated for non-bulk domestic ground shipments for packaging of 450 liters (119 gallons) or less (DOT 49CFR 173.150 (f)).

IMO/IMDG: UN1263, Paint (CONTAINS 1-Methoxy-2-Propyl Acetate), 3, PG III, Marine Pollutant

SECTION 15: REGULATORY INFORMATION

Regulatory Lists

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory or exempt from listing on the TSCA Inventory.

SARA 311/312 Categories

Acute: Yes **Chronic:** Yes **Fire:** Yes **Pressure:** Yes **Reactive:** Yes

This product contains the following Sara, Title III, Section 313 Chemicals:

Aliphatic Diisocyanate CAS# 5124-30-0

Regulatory List for State: FL, MA, MN, PA, RI

California Proposition 65 Information: Warning! This product contains detectable components, including the following components, which are substances or belong to classes of substances known to the State of California to cause cancer, birth defects and/or other reproductive harm.

Aliphatic Diisocyanate CAS# 5124-30-0

Canadian Regulations

DSL/NDSL: The components of this product are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substance List (NDSL).

WHMIS Hazard Class: B3 D2A

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Other Regulations: No other information available

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate. However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation