## Prepare/Maintenance Products



### Repair, Seal, Prep Products

Available products for use in repair, surface prep and maintenance of concrete.



# **Crack Repair**

These crack fillers and concrete repair products are designed for repairing crack and defects in concrete or masonry. We have several formulations, including repairs for both horizontal and vertical applications.







#### 818 Epoxy Crack Filler

- 100% solids epoxy crack filler
- Horizontal or vertical application
- 1:1 mix ratio
- Can be topcoated immediately



#### 821 Low Modulus Fast Set Gel

- 100% solids epoxy gel
- Horizontal or vertical application
- 1:1 mix ratio
- Fast set gel- consistency of petroleum jelly



### 601/602 Underwater Repair

- 601: Pourable crack filler
- 602: Crack filler paste
- 2:1 mix ratio
- Designed for underwater repairs

#### 929 Novolac Crack Filler


- 100% solids novolac crack filler (gel)
- Horizontal/vertical application
- 2:1 mix ratio
- Designed for chemical exposure areas

#### 443 Crack and Spall Repair

- Polyurethane hybrid quick repair
- Repair of hairline cracks, spalls in concrete
- 1:1 mix ratio, dual cartridge system
- Wide temp. application range: 0° to 110° F

### 343 Concrete Quick Fix Patch Kits

- Hybrid urethane packaged with sand
- 1:1 mix ratio
- Cures in temps as low as 20°F
- Quick repair of cracks and spalls







# Joint Sealants



These joint sealants exhibit excellent flexibility and are available in both vertical and horizontal formulations. Several variations are available to meet the needs of your next project.

829 Flexible Joint Sealant		830 Fast Set Flexible Jo	oint Sealant
<ul> <li>Excellent flexibility</li> <li>1:1 mix ratio</li> <li>Exceptional adhesion</li> <li>Pourable sealant</li> </ul>	٠ •	Excellent flexibility 1:1 mix ratio Fast set sealant Tube sets & kits	
829HV Flexible Vertical Joint Sealar	t l	928 Chemical Joint	Sealant
<ul> <li>Excellent flexibility</li> <li>1:1 mix ratio</li> <li>Vertical formulation</li> <li>Marginal trowel, putty knife</li> </ul>	[]	Excellent flexibility 4:1 mix ratio Pourable sealant Chemical exposure areas	
<ul> <li>928HV Chemical Vertical Sealant</li> <li>Excellent flexibility</li> <li>4:1 mix ratio</li> <li>Marginal trowel, putty knife</li> <li>Vertical chemical exposure areas</li> </ul>			
Refer to individual tech data for complete details.			

## **Special Use Prep Products**



**MOISTURE VAPOR BARRIER** 

409, Moisture Vapor Barrier is a two component 100% solids epoxy seal that can help control moisture vapor emission rates up to 20lb/24hr/1000 sq. ft.

This primer can help alleviate some of the issues associated with moisture vapor in concrete. Meets the ASTM F3010 product requirements for vapor permeance at the recommended thickness.



820, Oil Stop Epoxy Primer exhibits excellent characteristics for coating over petroleumbased oil contaminated concrete. It allows for excellent substrate penetration that results in outstanding adhesion.

This product is an ideal primer for automotive service bays or machine shop floors prior to applying a suitable flooring system.



MORE THAN JUST A PRODUCT... Services and Solutions for Building Your Business 800.831.5600 • www.nationalpolymers.com

6/2019